

Marked-Up Version of Substitute Specification

Description

~~Method and data system for connecting a wireless local network to a UMTS terminal station~~

SPECIFICATION

TITLE OF THE INVENTION

METHOD AND DATA SYSTEM FOR CONNECTING A WIRELESS LOCAL NETWORK TO A UMTS TERMINAL STATION

BACKGROUND OF THE INVENTION

~~The present invention relates to a method and a data system for connecting a wireless local network to a UMTS terminal station.~~

Wireless networks, known as WLANs (Wireless Local Area Networks), are increasingly being installed in small, local areas known as “hot spots” such as, for example, airports, hotels or similar areas with a high subscriber density. Because of the technical possibilities afforded by WLAN it is desirable to use this technology as an add-on to mobile radio systems of the third generation such as, for example, UMTS (Universal Mobile Telecommunications System).

Figure 1 shows the basic principle of a WLAN network architecture in a schematic representation. It depicts a wireless local communication network in which mobile stations MTs (Mobile Terminals) are connected by radio via a ~~number~~plurality of access nodes APs (Access Points) to a broadband data network (BDN). The access nodes APs are WLAN base stations. Each access node AP supplies all the mobile terminals MTs contained in a cell. In this ~~case~~case the cell size ~~may~~can extend to a maximum of several hundred meters. In ~~principle~~principle WLANs can be used to build a cellular radio network in which an existing data connection can be handed on from access node to access node in line with the movement of the mobile terminals MT. In mobile radio contexts this is generally known as “roaming”. The maximum data rates are dependent on the respective WLAN technology and can range up to 54 Mbit/s.

To connect a WLAN in UMTS, an architecture is known in which WLAN and UMTS represent autonomous systems that are connected to each other via an

interworking unit (IWU). Figure 2 shows this known network architecture in a schematic representation. The purpose of the element IWU is to convert signaling and user data from WLAN to UMTS and vice versa. The WLAN is represented with the elements AP, router and AAAL. The APs ~~are~~ are in ~~turn~~ turn access nodes, the router is a switching processor and the AAAL (Authentication Authorization Accounting Local) is a local computer which is used for authentication, authorization and accounting. The network architecture of UMTS is shown with the elements NodeB, RNC, SGSN, GGSN and HSS. NodeB is a UMTS base station, the RNC (Radio Network Controller) is a radio network control element, SGSN (Serving GPRS Support Node) and GGSN (Gateway GPRS Support Node) are GPRS support nodes and the HSS (Home Subscriber Server) is a local subscriber computer. GPRS (General Packet Radio Service) is a mobile radio standard according to which a dedicated data connection is not set up for each subscriber, but instead the total number of available transmission resources is allocated as needed to the individual subscribers, and the data is transmitted in packets.

In the ~~UMTS~~ UMTS the actual terminal station, designated in the diagram as user facility UE (User Equipment), consists of the mobile facility ME (Mobile Equipment) and the physical chip card UICC (Universal Integrated Circuit Card). Figure 3 shows the corresponding layout ~~of of~~ a user equipment UE in schematic form. The USIM (Universal Subscriber Identity Module) together with the USAT functionality (USIM Application Toolkit) is implemented as standard on the UICC. The USIM corresponds to the SIM (Subscriber Identity Module) in the second-generation mobile radio standard GSM (Global System for Mobile Communications). The USIM enables a mobile radio subscriber to use his or her ME in a UMTS radio network. All the important data of the subscriber access is stored on the USIM, ~~such said~~ data serving to identify and to prove the access authorization, that is to say authentication, of the mobile radio subscriber, as well as to ensure encryption and decryption of the user data as protection against eavesdropping and tampering or corruption. The USAT functionality enables the ME to be configured directly via the UMTS radio network. Technical specification

TS 31. 111 Version 4. 5. 0 (2001-12) "USIM Application Toolkit (USAT)" of the 3rd Generation Partnership Project (3GPP) deals with the interface between the ME and the UICC and essentially ~~includes~~comprises a list of commands which the ME can convert interactively with the UICC.

With the desired connection of WLAN in UMTS there is, however, ~~however~~ the problem that frequent connection setups and/or clear-downs are necessary due to the non-permanent availability of the WLAN. Known procedures are handicapped ~~by~~by a high signaling overhead or often cannot guarantee reliable connection setup and/or clear-down. Furthermore, because of the USIM/USAT standardization in UMTS, an existing data connection in the WLAN should be monitored by the USIM/USAT of the UMTS terminal station. However, an implementation of a corresponding ~~process~~means of control is not known to date.

~~The~~The object of the present invention ~~is~~, is therefore, directed toward ~~to~~ provide a method and a data system for connecting a wireless local network to a UMTS terminal station with USIM/USAT functionality which enables an exchange of WLAN-specific data between a UMTS terminal station and UICC and, ~~and~~ in addition, ~~addition~~ guarantees reliable connection setup and/or clear-down.

~~This object is achieved according to the invention by a method for connecting a wireless local network to a UMTS terminal station with USIM/USAT functionality having the features of claim 1 and a data system for connecting a wireless local network to a UMTS terminal station having the features of claim 8. In addition, a terminal station having the features of claim 15 represents an achievement of the object. The subclaims each define preferred and advantageous embodiments of the present invention.~~

SUMMARY OF THE INVENTION

Accordingly, the ~~The~~ inventive method for connecting a wireless local network to a UMTS terminal station with USIM/USAT functionality includes~~comprises~~ the following method steps:

monitoring~~Monitoring~~ of the activity of the local network by the terminal station,~~station,~~

~~transmission~~Transmission of the type and/or the identity number of the local network to the terminal station following successful detection of local network activity;~~activity;~~

~~initiation~~Initiation of a logical connection between the local network and the terminal station;~~station;~~ and

~~polling~~Polling of the specific subscriber data of the local network.

The wireless local network is preferably implemented using WLAN technologies which support broadband radio access to broadband data networks. ~~Furthermore,~~Furthermore the wireless local network is preferably based on the TCP/IP (Transmission Control Protocol/Internet Protocol), ATM (Asynchronous Transfer Mode), or B-ISDN (Broadband Integrated Services Digital network) standard. Examples of broadband WLAN technologies are IEEE 802.11, Hiperlan/2, Openair or SWAP. In the present ~~context,~~context WLAN is used as a synonym for all broadband WLAN technologies.

In an ~~embodiment,~~a development of the present ~~invention,~~invention the temporary status of the local network and/or specific subscriber data of the local network is polled at periodic intervals. Corresponding polling cycles are preferably performed during an existing WLAN connection.

In a preferred ~~embodiment,~~embodiment the specific subscriber data includes the data: type/identity number, subscriber identification, password, secret key for encrypting and decrypting data, and address of an access node.

~~Furthermore,~~Furthermore it is possible that the WLAN-specific data of the subscriber access which is used for identification and authentication of the mobile radio ~~subscriber,~~subscriber as well as the encryption and decryption of the user data to protect against eavesdropping and tampering or ~~corruption,~~corruption is stored on the physical chip card UICC of the UMTS terminal station. For example, in order to monitor the connection setup and/or clear-down of an existing data connection in the WLAN the WLAN-specific data of the subscriber access can be requested and stored in the UMTS terminal station by the UICC.

In ~~another embodiment,~~a development of the present ~~invention,~~invention the monitoring of the activity of the local network and the transmission of the data

to the terminal station is initiated by a universal chip card which is installed in the terminal device. ~~Preferably,~~ Preferably the universal chip card is the UICC. Furthermore the universal chip card preferably notifies the terminal station of a deactivation of the local network.

In ~~a further embodiment a development~~ of the present ~~invention,~~ invention the universal chip card initiates a clear-down of the logical connection between the local network and the terminal station. ~~Furthermore,~~ Furthermore the terminal station preferably acknowledges all the data transmitted. An acknowledgment of this kind ~~can~~ additionally may be used to transmit further information.

The ~~present invention also provides~~ ~~the aforementioned object is also achieved~~ by a data system for connecting a wireless local network to a UMTS terminal station, ~~the~~. The data system including has

a local ~~network;~~ network;

a UMTS terminal station with USIM/USAT functionality which is suitable for establishing a connection to the local ~~network;~~ network;

parts means for monitoring the activity of the local network, the parts for monitoring being said ~~means being~~ contained in the terminal ~~station;~~ station;

parts means for transmitting the type and/or the identity number of the local network to the terminal station, with the transmission taking place following successful detection of local network ~~activity;~~ activity;

parts means for initiating a logical connection between the local network and the terminal ~~station;~~ station; and

parts means for polling the specific subscriber data of the local network.

The ~~present object of the invention~~ further provides ~~is also achieved by a~~ terminal station, ~~more particularly a mobile radio terminal device~~, for use in a method according to the present invention and/or for use in a data system according to the present invention.

~~The invention will be explained below with reference to the attached drawings and on the basis of exemplary embodiments. The features represented therein and also the features already described above can be essential to the~~

~~invention not only in the cited combination but also individually or in other combinations. The figures show:~~

Additional features and advantages of the present invention are described in, and will be apparent from, the following Detailed Description of the Invention and the Figures.

BRIEF DESCRIPTION OF THE FIGURES

Figure 1 shows a schematic representation of a WLAN network ~~architecture.~~

Figure 2 shows a schematic representation of a UMTS/WLAN network ~~architecture.~~

Figure 3 shows a schematic representation of a mobile radio terminal device with a UICC ~~card.~~

Figure 4 shows a schematic representation of a UMTS user ~~unit.~~

Figure 5 shows an exemplary embodiment of an information flow between UICC and ME.

DETAILED DESCRIPTION OF THE INVENTION

Figures 1 to 3 have already been explained in the Background section of the present application,~~introduction to the description~~ so reference will be~~is~~ made to the corresponding embodiments.

Figure 4 shows a schematic representation of a UMTS user unit. The physical chip card UICC (Universal Integrated Circuit Card) includes USIM and USAT. The UICC is connected to the mobile equipment ME via a communication interface Cu. ~~The~~~~Said~~ mobile equipment ME is connected,~~connected~~ in turn,~~turn~~ to a WLAN module WM via the communication interface Cw. In the UMTS ~~unit,~~ the hardware-side WLAN connection can be implemented by a corresponding module in a form whereby the module is either already integrated therein as a WLAN radio part or can be inserted as a WLAN PC card into the corresponding interface of the ~~station;~~~~station,~~ for ~~example,~~~~example~~ in the form of a PCMCIA (Personal Computer Memory Card International Association) interface.

Figure 5 shows an exemplary embodiment of an information flow between a physical chip card UICC and a mobile equipment ME. It is assumed in this case

that a mobile radio subscriber is at a location at which he or she has access to a UMTS and a WLAN radio network. His or her mobile radio terminal device consists of the components UICC, ME and WM (compare Figures 3 and 4). It is further assumed that a network architecture is present wherein WLAN and UMTS are connected as shown in Figure 2. It is ~~also further~~ assumed that the subscriber is registered in the UMTS network with his or her UMTS terminal station and wants to set up an Internet connection ~~viaby means of~~ a WLAN based on the IEEE 802.11 technology. Toward that ~~end~~ the subscriber must first identify and authenticate himself/herself to the WLAN network. He/she does this by keying his/her name for the purpose of subscriber identification and his/her password for the purpose of authentication into a corresponding input menu of his/her terminal station. This is registered by the WLAN module WM ~~and~~ and if the details are input ~~correctly, correctly~~ the subscriber ~~can now~~ may set up an Internet connection by WLAN.

In order to monitor the connection setup and cleardown ~~as well as~~ and also an existing data connection in the WLAN, the WLAN-specific subscriber data is requested and stored by the UICC. Figure 5 shows an exemplary embodiment of the corresponding information flow between UICC and ME. It is assumed here that the interface Cw according to Figure 4 is implemented in such a way that it supports the information flow across the interface Cu in a suitable manner.

In step 1 shown in Figure 5, ~~the~~ UICC directs the ME to monitor the “Active” status of the WLAN module WM. As a response 2 ~~thereto, thereto~~ the ME sends a positive reception acknowledgement. Following occurrence of the event, that is to say the activation of the WLAN module WM as a result of a connection setup, the ME sends a response 3 containing the set parameters “Status = Active,” “WLAN type/identity number = IEEE 802.11” to the UICC. Before the actual polling of the WLAN-specific subscriber data can take place, a logical connection is initiated. This is implemented by the UICC with the request 4 and the set parameter “WLAN type/identity number = IEEE 802.11” to the ME. As the response 5 the ME notifies the UICC ~~viaby means of~~ the set parameters “Status = OK” and “WLAN type/identity number = IEEE 802.11,” as an

acknowledgement, that the request has been executed. ~~Pursuant to~~~~By means of~~ the request ~~6.6~~ the UICC then interrogates the ME for the subscriber data of the WLAN module. The ME's response 7 contains the corresponding information: WLAN type/identity number, subscriber identification, password, secret key for data encryption and decryption, and Internet protocol address of the access node AP. In the case of the connection clear-down, that is to say the deactivation of the WLAN module, the ME sends a response 8 containing the set parameters "Status = Not Active," WLAN type/identity number = IEEE 802.11" to the UICC. To terminate the logical connection, the UICC sends the command 9 containing the set parameter "WLAN type/identity number = IEEE 802.11" to the ME. Finally, with the response 10 and the status field "OK," the ME notifies the UICC that the request has been executed and the logical connection terminated.

During an existing WLAN connection, that is to say between the steps 7 and 8, it is also possible that the UICC polls the temporary status of the WLAN module or, as the case may be, the WLAN-specific subscriber data at periodic intervals.

In the exemplary ~~embodiment~~, ~~embodiment~~ it was assumed that the interface Cw is already implemented in such a way that it can support the data exchange via the interface Cu (compare Figure 4). Six USAT commands are defined for the purpose of implementing the data exchange between UICC and ME via the interface ~~Cu~~:Cu:

1) ~~Request the WLAN status: Pursuant to~~~~By means of~~ this ~~command,~~~~command~~ the UICC can interrogate the ME for the status, ~~such as for example~~ "Active" or "Not Active" and type or identity number of the WLAN module, ~~such as for example~~ IEEE 802.11 or Hiperlan/2. As ~~at the response thereto,~~~~thereto~~ the ME is expected to send the corresponding information to the UICC via the command "terminal response,". This command has the parameters status and WLAN type/identity number.

2) ~~Request WLAN information: Pursuant to~~~~By means of~~ this ~~command,~~~~command~~ the UICC can interrogate the ME for the WLAN-specific subscriber data of the WLAN module. As ~~at the response thereto,~~~~thereto~~ the ME is expected to send the corresponding information to the UICC via the command

“terminal response.” This command ~~includes~~comprises the parameters WLAN type/identity number, subscriber identification, password, secret key for data encryption and decryption, and Internet protocol address of the access node AP. This command corresponds to step 6 in Figure 5.

3) Connect WLAN: ~~Pursuant to By means of this command,~~command the UICC can instruct the ME to initiate a logical connection to the WLAN module. As a response ~~thereto, thereto~~ the ME is expected to notify the UICC ~~viaby means~~ of the command “terminal response” whether the request could be executed or not. This command has the parameter WLAN type/identity number and corresponds to step 4 in Figure 5.

4) Disconnect WLAN: ~~Pursuant toBy means of this~~ ~~command,~~command the UICC instructs the ME to terminate a logical connection with the WLAN module. As a response thereto the ME is expected to notify the UICC ~~viaby means of~~ the command “terminal response” whether the request could be executed or not. This command has the parameter WLAN type/identity number and corresponds to step 9 in Figure 5.

5) Set up an event list: ~~Pursuant toBy means of this~~ ~~command,~~command the UICC instructs the ME to monitor the status of the WLAN ~~module; module,~~ for ~~example, example~~ “Active.” As a direct response ~~thereto, thereto~~ the ME is expected to send a “terminal response” containing “Accepted” or “Not accepted” to the UICC as an acknowledgement of the command. If the event occurs, that is to say in the case of the activation of the WLAN module, the ME is expected to send the corresponding information to the UICC ~~viaby means of~~ the command “terminal response.” With this ~~command,~~command the WLAN-specific status parameters are added to the already existing parameter ~~list; list,~~ that is to say, event list. This command corresponds to step 1 in Figure 5.

6) Terminal response: This is a command ~~by means of~~ which the ME is expected to respond accordingly to the requests of the UICC concerning the above defined WLAN-specific commands. In the ~~process, process~~ the WLAN-specific parameters (~~i.e., i.e.~~ status, WLAN type/identity number, subscriber identification,

password, secret key for data encryption and decryption, and Internet protocol address of the access node APAP, are added to the already existing parameter list. This command corresponds to steps 2, 3, 5, 7, 8 and 10 in Figure 5.

The following table shows in summary form the list of new commands together with parameter, source and destination:

Command	Parameter	Source	Destination
Request WLAN status	Status WLAN type/identity number	UICC	ME
Request WLAN information	WLAN type/identity number Subscriber identification Password Secret data encryption and decryption key IP address of the AP	UICC	ME
Connect WLAN	WLAN type/identity number	UICC	ME
Disconnect WLAN	WLAN type/identity number	UICC	ME
Set up an event list	Status	UICC	ME
Terminal response	Status WLAN type/identity number Subscriber identification Password Secret data encryption and decryption key IP address of the AP	ME	UICC

Although the present invention has been described with reference to specific embodiments, those of skill in the art will recognize that changes may be made

thereto without departing from the spirit and scope of the present application as set forth in the hereafter appended claims.

ABSTRACT OF THE DISCLOSURE

~~A~~The invention relates to a method is provided for connecting a wireless local network (WLAN) to a UMTS terminal station (ME) having USIM/USAT functionality, ~~including~~comprising the following method steps: monitoring the activity of the local network via the terminal station; transmitting the type and/or identity number of the local network to the terminal station once the activity of the local network has been successfully detected; initiating a logical link between the local network and the terminal station, and; querying the specific subscriber data of the local network. In ~~an~~a preferred embodiment of the present invention, the temporary status of the local network and/or specific subscriber data of the local network are/is queried at periodic intervals.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of claims:

Claims 1-15 (canceled)

Claim 16 (new): A method for connecting a wireless local network to a UMTS terminal station having USIM/USAT functionality, the method comprising:

- monitoring activity of the wireless local network by the terminal station;
- transmitting at least one of a type and an identity number of the wireless local network to the terminal station following successful detection of local network activity;
- initiating a logical connection between the wireless local network and the terminal station; and
- polling specific subscriber data of the wireless local network.

Claim 17 (new): A method for connecting a wireless local network to a UMTS terminal station as claimed in claim 16, wherein a temporary status of at least one of the wireless local network and the specific subscriber data of the wireless local network is polled at periodic intervals.

Claim 18 (new): A method for connecting a wireless local network to a UMTS terminal station as claimed in claim 16, wherein the specific subscriber data of the wireless local network includes a type/identity number, a subscriber identification, a password, a secret key for data encryption and decryption, and an address of an access node.

Claim 19 (new): A method for connecting a wireless local network to a UMTS terminal station as claimed in claim 16, wherein the steps of monitoring and transmitting are initiated by a universal chip card installed in the terminal station.

Claim 20 (new): A method for connecting a wireless local network to a UMTS terminal station as claimed in claim 19, wherein the terminal station notifies the universal chip card of a deactivation of the wireless local network.

Claim 21 (new): A method for connecting a wireless local network to a UMTS terminal station as claimed in claim 20, wherein the universal chip card initiates a cleardown of the logical connection between the wireless local network and the terminal station.

Claim 22 (new): A method for connecting a wireless local network to a UMTS terminal station as claimed in claim 16, wherein the terminal station acknowledges all data transmitted.

Claim 23 (new): A data system for connecting a wireless local network to a UMTS terminal station, comprising:

- a wireless local network;
- a UMTS terminal station having USIM/USAT functionality and being suitable for establishing a connection to the wireless local network;
- parts for monitoring activity of the wireless local network, the parts for monitoring being contained in the terminal station;
- parts for transmitting at least one of a type and an identity number of the wireless local network to the terminal station, the transmission occurring following successful detection of local network activity;
- parts for initiating a logical connection between the wireless local network and the terminal station; and
- parts for polling specific subscriber data of the wireless local network.

Claim 24 (new): A data system for connecting a wireless local network to a UMTS terminal station as claimed in claim 23, wherein the terminal station is suitable for polling a temporary status of at least one of the wireless local network and the specific subscriber data of the wireless local network at periodic intervals.

Claim 25 (new): A data system for connecting a wireless local network to a UMTS terminal station as claimed in claim 23, wherein the specific subscriber data includes a type/identity number, a subscriber identification, a password, a secret key for data encryption and decryption, and an address of an access node.

Claim 26 (new): A data system for connecting a wireless local network to a UMTS terminal station as claimed in claim 23, wherein the terminal station further comprises a universal chip card which initiates the monitoring of the activity of the wireless local network and the transmission of data to the terminal station.

Claim 27 (new): A data system for connecting a wireless local network to a UMTS terminal station as claimed in claim 26, wherein the terminal station is suitable for notifying the universal chip card of a deactivation of the wireless local network.

Claim 28 (new): A data system for connecting a wireless local network to a UMTS terminal station as claimed in claim 27, wherein the universal chip card is suitable for initiating a clear-down of the logical connection between the wireless local network and the terminal station.

Claim 29 (new): A data system for connecting a wireless local network to a UMTS terminal station as claimed in claim 23, wherein the terminal station is suitable for acknowledging all data transmitted.

Claim 30 (new): A UMTS terminal station having USIM/USAT functionality and being suitable for establishing a connection to a wireless local network, comprising:

parts for monitoring activity of the wireless local network;

parts for initiating transmission of at least one of a type and an identity number of the wireless local network to the terminal station, the transmission occurring following successful detection of local network activity;

parts for initiating a logical connection between the wireless local network and the terminal station; and

parts for polling specific subscriber data of the wireless local network.

REMARKS

The present amendment makes editorial changes and corrects typographical errors in the specification, which includes the Abstract, in order to conform the specification to the requirements of United States Patent Practice. No new matter is added thereby. Attached hereto is a Substitute Specification including a marked-up version of the changes made thereto via the present amendment.

In addition, the present amendment cancels original claims 1-15 in favor of new claims 16-30. Claims 16-30 have been presented solely because the revisions by red-lining and underlining which would have been necessary in claims 1-15 in order to present those claims in accordance with preferred United States Patent Practice would have been too extensive, and thus would have been too burdensome. The present amendment is intended for clarification purposes only and not for substantial reasons related to patentability pursuant to 35 U.S.C. §§101, 102, 103 or 112. Indeed, the cancellation of claims 1-15 does not constitute an intent on the part of the Applicants to surrender any of the subject matter of claims 1-15.

Early consideration on the merits is respectfully requested.

Respectfully submitted,

BELL, BOYD & LLOYD LLC

BY 

William E. Vaughan

Reg. No. 39,056

P.O. Box 1135

Chicago, Illinois 60690-1135

Phone: (312) 807-4292

Dated: January 24, 2005